



Thermal Transfer Overprinting

Videojet 6230

The Videojet 6230 delivers easy usability with built-in Code Assurance to help significantly reduce costly coding errors when marking onto flexible packaging.

Achieve increased reliability and improved code quality with the Videojet 6230 Thermal Transfer Overprinter (TTO). An airless printer for the most versatile production line installation, the 6230 features built-in code assurance and simple usability to help reduce flexible packaging coding error.

Code assurance comes as standard in the Videojet 6230 printer when using templates created by CLARISOFT™ or VideojetConnect™ Design software*. These simple code creation tools help reduce operator interactions resulting in fewer user errors and unnecessary product waste and rework. Available with Bluetooth® connectivity**, the 6230 printer can be controlled from an Android phone***, simplifying operator interaction with the production line.



Simple usability

- Simple change ribbon cassette, with pushbutton lock mechanism, allows for fast and easy ribbon replacement
- Intuitive tablet-like 5" touchscreen controller with CLARITY™ interface used in other Videojet technologies

Built-in productivity

- Precise ribbon control with bidirectional stepper motors minimizes gaps between codes and reduces ribbon wastage
- 700m ribbon length requires fewer ribbon changes versus hot stamp or other competitive TTO systems
- Simple ribbon path that ensures fast changeovers and a more efficient operation
- Bluetooth® connectivity allows operator to control printer from an Android phone

Fits your unique production needs

- Airless operation removes the need for plant air
- Offers high-quality codes up to speeds of 150 packs / minute
- Single design printhead for intermittent or continuous printing
- Compact design easily integrates into most production lines

Code Assurance

- WYSIWYG print preview allows operators to confirm the correct code is selected
- Built-in Code Assurance software helps to reduce operator-induced errors, decreasing unnecessary product waste and rework
- Real-time clock stamp avoids date errors
- Benefit from simple code creation with VideojetConnect Design or CLARISOFT software

* Subject to availability in your country

** A Bluetooth USB Adapter is required when using the Videojet 6230 App. The Videojet 6230 printer is warranted to work only with the recommended Videojet supplied Bluetooth USB Adaptors that comply with the applicable FCC or CE regulations. Please check with your local authorities to determine if additional country-specific certification is required for your country.

*** The Videojet 6230 app supports Android OS, Version 4.4.4 (KitKat) or higher. The Android phone is required to allow Bluetooth tethering when using the Videojet 6230 App.

Videojet® 6230

Thermal Transfer Overprinting

Printhead

32mm, 200 dpi (8 dots/min)

Print Area

Continuous mode: Max. 32mm x 100mm (1.26" x 3.93")
Intermittent mode: Max. 32mm x 47mm (1.26" x 1.85")

Printing Modes

Continuous & Intermittent modes in the same machine

Print Speed

Intermittent: 50mm/sec. to 300mm/sec. (2.0"/sec to 11.8"/sec)
Continuous: 40mm/sec. to 500mm/sec. (1.6"/sec to 19.7"/sec)

Operator Interface

5.0" Color QVGA CSTN LCD and touch screen (800 x 480 pixels)
WYSIWYG print preview
On-board diagnostics
3 levels of password protection
Multiple language support

Ribbon Drive

Solid-state, clutchless bi-directional ribbon drive, including

- Ribbon break detection
- End of reel detection
- Ribbon consumption indication
- Ribbon Saving Mode: Radial

Printing Capabilities

Full downloadable font support using Windows® TrueType® fonts
Fixed and variable text and numeric data
User entered text and numeric data (including Chinese)
Flexible date / time formats (based on internal real time clock)
Auto best before date calculations
Flexible shift code formats

Bar Codes

EAN8, EAN13, UPCA, UPCE and QR codes

Ribbon Length

700 meters (766 yds.) maximum, available in variety of grades and colors

Ribbon Widths

0.8" (20mm) min, 1.3" (33mm) max

Image Management

Design

Videojet CLARISOFT™ CLARISUITE™ or VideojetConnect™ Design Template Management software

Storage

Internal memory 30 MB, expandable to 4GB

Message upload

USB memory stick

Ethernet

RS232

Videojet 6230 App* via Bluetooth**

* The Videojet 6230 app supports Android OS, Version 4.4.4 (KitKat) or higher. The Android phone is required to allow Bluetooth tethering when using the Videojet 6230 App.

** A Bluetooth USB Adapter is required when using the Videojet 6230 App. The Videojet 6230 printer is warranted to work only with the recommended Videojet supplied Bluetooth USB Adaptors that comply with the applicable FCC or CE regulations. Please check with your local authorities to determine if additional country-specific certification is required for your country.

Network Management Software

CLARINET™

Remote Coder Configuration Software

CLARITY™ Configuration Manager (included)

External Communications

USB memory stick, ethernet, RS232, ASCII and binary communications

External Inputs

Print Go
Inhibit Print
Encoder (single phase or quadrature)

External Outputs

Fault
Warning
Busy
Printing

Standard installation options master/follower configuration

Up to four Videojet 6230 printers controlled via a single CLARITY™ control unit


Power Supply

100-240 VAC, 50/60Hz, 24V (120W) 5A


Operating Temperature

32°-104°F (0°- 40° C)

Printer body



Control panel



CERTIFIED
ISO 9001
DOCUMENTED QUALITY



Call (65) 6444 4218

Email marketing.singapore@videojet.com

or visit www.videojet.sg

Videojet Technologies (S) Pte Ltd
No. 11 Lorong 3 Toa Payoh
Block B #03-20/21 Jackson Square
Singapore 319579

© 2018 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Computer, Inc. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.

Part No. SL000662
ss-6230-en-sg-0818

